

Safety, speed and control with your comfort in mind

Maximum benefits for all users

For lift passengers:

- Smooth starting and stopping
- Fluid movements
- Optimum speed (minimum travel time)
- Accurate stopping
- Silent operation

For the service technician:

- Communication tools adaptable to each application (PC, remote graphic display terminal and Simple Loader®)
- Ease of maintenance:
 - monitoring menu data includes distance travelled, number of journeys, etc.
 - diagnostics menu provides a list of faults and their context (lift car speed, line voltage, motor current, etc.)

For the building owner:

- Reduced machine wear due to fewer mechanical shocks
- Greater energy savings achieved by optimising drive power consumption

5 seconds

to duplicate your drive configuration with Simple Loader

Up to 50%

energy savings

Precision and durability for your lift applications



Altivar LIFT

Variable speed drives for synchronous and asynchronous motors (with or without encoder)

- 200/240 V range - 27 A to 66 A
- 380/480 V range - 10 A to 48 A

Schneider Electric Industries SAS

Head office:
35 rue Joseph Monier
CS 30323
92506 Rueil-Malmaison Cedex
France

www.schneider-electric.com

ART: 838013

Due to possible changes in standards and equipment, the features described in this document in the form of text and images are subject to confirmation by Schneider Electric.

Designed and created by: Gavrinis
Photos: Schneider Electric - Shutterstock
Printed by:

07/2010

DIA2ED1101201EN

Schneider
Electric

Make the most of your energy

Tougher
More powerful
Safer

Acceleration and deceleration to the nearest millimetre

Plug & Play installation

- Dedicated Lift menu for installers
- Lift-specific units (kg, cm, m/s, m/s², etc.)

Communication tools

for customised setup:

- Remote graphic display terminal
- Multi Loader
- Simple Loader
- PowerSuite software

Hardware specially designed to:

- Handle the specific constraints of lift applications (repetitive starting/stopping, equipment power always on, control at 0 Hz, etc.)
- Comply with lift standards (EN 12015 and EN 12016 without external filter)
- Prevent vibration during operation (optimised current measurements)

All-round high performance

- Lift ramp allows simple adjustment for optimum comfort
- Passenger comfort on starting regardless of the type and age of lift (load measurement and rollback management)
- Wide choice of encoders for any type of motor
- Option to perform static angle test for synchronous motors on existing lifts

Integrated safety

- Power Removal® function certified for use with a single motor contactor



Remote communication - use the remote graphic display terminal to configure and communicate with the drive, even when the enclosure is closed.

Quick configuration and communication with PowerSuite software and Multi Loader. Configurations can be duplicated in just a few seconds using Simple Loader.



Carry out maintenance without interrupting operation

Synchronous open loop operation in degraded mode means, for example, that the lift car can be moved to a position of safety when the encoder is not operating.



6 languages available as standard

You can use your graphic display terminal to customise menus, create shortcuts using the function keys and save configurations, among many other things.

Selection guide

Altivar LIFT - 380...480 V - three-phase

Motor	Altivar LIFT				
Nominal current	Maximum continuous current		Maximum transient current	Reference	Dimensions in mm (WxHxD)
	380 V	460 V			
A	A	A	A		
10	10.5	7.6	14.3	ATV71LD10N4Z	175x295x161
14	14.3	11	19.4	ATV71LD14N4Z	175x295x161
17	17.6	14	23.9	ATV71LD17N4Z	210x295x187
27	27.7	21	37.7	ATV71LD27N4Z	230x400x187
33	33	27	44.9	ATV71LD33N4Z	230x400x187
48	48	40	65.3	ATV71LD48N4Z	240x550x230

Altivar LIFT - 200...240 V - three-phase

Altivar LIFT				
Motor	Altivar LIFT			
Nominal current	Maximum continuous current	Maximum transient current	Reference	Dimensions in mm (WxHxD)
	230 V			
A	A	A		
27	27.5	37.4	ATV71LD27M3Z	230x400x187
33	33	44.9	ATV71LD33M3Z	230x400x187
54	54	73.4	ATV71LD54M3Z	240x420x210
66	66	89.8	ATV71LD66M3Z	240x420x210

Technical characteristics

Lift function Output contactor control Output contactor feedback Inspection mode Half-floor control Direct to floor Brake control Deferred thermal stop Advanced detection of output phase loss Adjustable noise level Evacuation with inverter Rollback management External load measurement Sheave protection Optimised speed loop Optimised ramp profile	Motor characteristics Asynchronous open loop Asynchronous closed loop Synchronous open loop Synchronous closed loop Static motor parameter identification Static angle test (synchronous motor) Encoder characteristics Incremental encoder SinCos, SinCos EnDat, SinCos Hiperface, SSI Resolver Encoder signal emulation Communication Modbus CANopen Ethernet, Profibus, DeviceNet, etc.
---	--

Option cards

Encoder interface cards	
RS 422 outputs, 5 V	VW3 A3 401
RS 422 outputs, 15 V	VW3 A3 402
Open collector outputs, 12 V	VW3 A3 403
Open collector outputs, 15 V	VW3 A3 404
Push-pull outputs, 12 V	VW3 A3 405
Push-pull outputs, 15 V	VW3 A3 406
Push-pull outputs, 24 V	VW3 A3 407
Resolver	VW3 A3 408
SinCos, SinCos Hiperface, EnDat, SSI	VW3 A3 409
Incremental with emulation RS422 outputs, 5 V or 15 V, with emulation	VW3 A3 411
I/O cards	
Logic I/O	
1 x 24 V voltage output 1 x 10 V voltage output 1 relay logic output 2 open collector assignable logic outputs 1 input for up to 6 PTC probes	VW3 A3 201
Extended I/O	
Same as logic I/O card + 2 analog inputs 2 analog outputs 1 frequency control input	VW3 A3 202
Programmable cards	
Controller Inside	VW3 A3 501
Accessories	
Remote graphic display terminal	VW3 A1 101
Simple Loader	VW3 A8 120
Multi Loader	VW3 A8 121
Modbus-Bluetooth® adaptor	VW3 A8 114
Software	
PowerSuite	VW3 A1 104
Update	VW3 A8 105